

WILSON & MORRIS

PITTURE DECORATIVE

Product Information Card

SILOX PRIMER WM

Fixative Acrilsilossanico water

Description

SILOX PRIMER WM by **Wilson & Morris** is a fixative concentrate of Acrylic-siloxane of high quality water-based, non-film-forming, consolidator and leveler for ceilings and walls in the interior. High penetrating power suitable for impregnation.

Use

SILOX PRIMER WM by **Wilson & Morris** can be applied on surfaces such as:
old plaster as a consolidator and smoother
new plaster as smoother absorbent
Lime plasters as a hardener

Application and Media Preparation

Make sure all surfaces are clean and free of grease or dust.
Dilute the product in ratio of 1 to 5 with water and apply by brush.
Verify through preliminary test directly on the wall if the dilution is sufficient to ensure that the translucent effect does not happen.
In this case, proceed with a higher dilution.
Pay more attention if you have to apply **SILOX PRIMER WM** by **Wilson & Morris** of lime plaster. Apply a first coat with a dilution ratio of 1 to 9 with water and then proceed with the normal of the primer drafting operations.
Finally, wait at least four hours with any water-based product.
Stir well before using.
Do not apply to fresh slightly acidic media, allow an adequate curing time, which can range from three to five weeks.

Warnings

Do not apply in the presence of temperatures below 8° C and above 30 ° C, and in conditions of excessive relative humidity conditions (<80%).
The material must be protected from frost and strong temperature changes during the entire application process.

Tool cleaning

Clean the tools immediately after use with hot and running water; use a detergent for best results. Is recommended to leave the tools submerged in clean water for about 12 hours.



Coverage

10-12 mq/lt per coat. The coverage varies according to surface.

Colors

Colorless

Packaging

Product packaging **SILOX PRIMER WM** by **Wilson & Morris** are 1 L, 5 L.

Storage

The material has a shelf life of 12 months in the jar, stored under cover, tightly sealed, original packaging, undiluted and at a temperature between + 5° C and + 35 ° C.

Product identification

Formulation: based on a mixture of acrylic copolymers in dispersion

Appearance: milky liquid

Appearance: Opaque

actual VOC content 1 g / L

Maximum allowed limit 30 g / L

Safety instructions

SILOX PRIMER WM by **Wilson & Morris** is an eco-friendly product, which complies with the regulations on volatile organic compounds (VOC) set by European legislation.

Ensure good ventilation during application and drying.

The product does not require labeling in accordance with D.L.65 of 14/03/03 and subsequent amendments. Use the product according to current standards of safety and hygiene. After use, do not litter containers in the environment. Allow the residue to dry before disposal in accordance with local regulations.

Keep out of reach of children. In case of contact with eyes, rinse immediately with plenty of water. In cases of ingestion, seek medical advice immediately and show the container and the data sheet.

Do not empty into drains, water courses and onto the ground.

For more information, refer to the MSDS.

The information in this data sheet are based on our best experience, they must be considered as general guidance and is given in good faith but without warranty; the card does not therefore imply any responsibility on the part of Wilson & Morris company for product applications outside of our direct control.

WILSON & MORRIS

PITTURE DECORATIVE

We accept no responsibility for the performance of products resulting from their use, beyond the value of the goods supplied by us. This does not affect your statutory rights.