

## Product Information Card

# STUCCO

## Inspired by stone finish

### Description

**STUCCO** by Wilson & Morris is a natural product consisting of slaked lime, colored acrylic and reinforced with natural earth oxides.

Based on the application process of the slaked lime, it can leave a smooth finish or not so smooth.

Any deformities on the surface are not to be considered as defects in the product, but typical elements and not subject to dispute.

It can be used on **MANTOVA** to get shiny marbled type finishes .

For interior walls.

### Application and preparation

Make sure all surfaces are clean and free of grease and dust.

On all surfaces, apply **SILOX PRIMER WM** (see product data sheet) to have an excellent uniformity, in order to get a full appearance of the color depth.

You may experience peeling if you proceed to repaint on precarious layers without primer paint.

Before applying on wet plaster make sure that they have taken hold.

Apply **STUCCO** with a trowel.

**STUCCO** is ready for use, if necessary add a small amount of water to bring it to consistency.

Mix the product until obtaining a homogeneous paste without lumps.

### Warnings

Do not apply at temperatures below the 5° C and above 40 ° C, and in conditions of excessive humidity conditions (<80%).

Make sure that the batch numbers are the same, or mix prior to use.

Check the color before use, as the company is not responsible for any additional costs arising from the misapplication of non-compliant colors.

The material must be protected from frost and strong temperature changes during the entire application process.

### Tool cleaning

Clean the tools immediately after use with hot and running water; use a detergent for best results.

## Consumption

0.5 Kg per meter by hand, consumption varies according to the roughness of the substrate.

## Colors

White or colored with colors of Wilson & Morris color folder.

## Packaging

The packages of the stucco product are: 2.5 Kg, 5 Kg.

## Storage

The material has a shelf life of 12 months in the jar, stored under cover, tightly sealed, original packaging, undiluted and at a temperature between + 5° C and +30 ° C.

## Product identification

Formulation: One component of lime.

Physical state: paste.

Appearance: Opaque.

Diffusion resistance factor: 30.

VOC content of 80 g / L.

Maximum allowed limit (grams per liter) 200 g / L.

Category

All Wilson & Morris products comply with laws regarding volatile organic compounds required by recent European regulations

## Safety instructions

Ensure good ventilation during application and drying.

The product does not require labeling in accordance with D. L. 65 of 14/03/03 and subsequent amendments. Use the product according to current standards of safety and hygiene. After use, do not litter containers in the environment. Allow the residue to dry before disposal in accordance with local regulations.

Keep out of reach of children. In case of contact with eyes, rinse immediately with plenty of water. In cases of ingestion, seek medical advice immediately and show the container and the data sheet.

Do not empty into drains, water courses and onto the ground.

For more information, refer to the MSDS.

WILSON & MORRIS

PITTURE DECORATIVE

---

The information in this data sheet are based on our best experience, they must be considered as general guidance and is given in good faith but without warranty; the card does not therefore imply any responsibility on the part of Wilson & Morris company for product applications outside of our direct control.

We accept no responsibility for the performance of products resulting from their use, beyond the value of the goods supplied by us. This does not affect your statutory rights.